








20345.S5



SIZE: 36 - 49



 PROTECTIVE COMPOSITE TOE	 ABRASION PROOF SOLE	 HOT/COLD INSULATION CI	 OIL RESISTANT SOLE FO FO	 NON-SLIP SOLE	 ANTISTATIC
 PROTECTIVE KEVLAR MIDSOLE	 SHOCK ABSORBER HEEL	 ELECTROSTATIC DISCHARGE	 ANTIBACTERIAL	 LIGHT WEIGHT	 WATER PROOF

	FEATURES	BENEFITS		
OUTER SURFACE	Polyurethane	Lightweight, flexible and air transfer providing structure.		
	Flexible Channel Surface Pattern	Esthetical and comfortable clothing.		
	Heel Support	Easy to remove and increase the heel resistance		
	Protective Pads	Provides maximum protection against bumps that may come from sides.		
TECHNOLOGY	Shock Absorber Heel	Provides abrasive resistance to sudden impacts on heel		
	Composite Toe	Resistant to 200 joule impacts that may come from toe.		
	Kevlar Midsole	Prevents cutter or piercing objects from damaging the sole of the foot.		
	Antibacterial inner Lining	Interior surface textiles used against bacteria that may form on your feet		
SOLE	Polyurethane and TPU Sole	Thanks to its lightness and TPU, it prevents the abrasion of the sole.		
	SRC Sole	SRA: Ceramic Surfaces + SRB: Metal Surfaces		
	Inner Sole	Comfortable, sweat absorber, antibacterial, antistatic and prevents odor.		
	Design	It provides resistance to scratching and easy cleaning.		
Areas of Usage	General Industry, Construction, Mining, Oil&Gas , Agriculture&Livestock			
HEAT AND ELECTRICITY	Resistant to-40C / 22.000V			
OTHER OPTIONS	 20345.S5	 20345.S4	 20347.05	 20347.04
WEIGHT (+/-) <small>*FOR SIZE 42</small>	1.96 kg	1.85 kg	1.82 kg	1.70 kg

