



<https://wearwell.com/>

## Diamond-Plate with Gritshield®

### Group 416

Wearwell's Diamond-Plate matting with GRITSCHILD® combines comfort with slip prevention particularly for oily overspray applications. **The tough gritted surface improves traction by 60%, protecting team members from dangerous slips and falls.**

The Nitrile enhanced Nitricell sponge absorbs repeated compression and bounces back to its original form better than any PVC sponge alternatives. The Nitricell sponge base is a Nitrile composite for exceptional comfort, rebound and long life. Beveled edges assure a perfect lay flat design to avoid trips. Sponge base extends to within 3 inches of the mat's surface edge for more standing area than other anti-fatigue mats.

- Gritted surface delivers 60% more traction
- Chemical and abrasion resistant
- 2X the resilience and 3X the life of off-brand products
- Maximized standing area for anti-fatigue and ergonomic support
- Floor mats are available in 15/16" thickness
- Lay-flat design prevents trip hazards
- One foot incremental lengths are available
- NFSI Certified
- Made in the USA
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

**Categories & Applications** Anti-Fatigue Matting

**Suitable Environment** Dry floors with an occasional spill. Avoid constant pooling fluids. Clean with a neutral PH cleaner., Slippery

**Customization Options** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Material** PVC Surface With Nitrile Infused Sponge

**Recycled** >50%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.10 / Wet COF = 1.0
Compression Deflection	ASTM D575 - 7.1psi @ 25% = .15" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU

UPC

Color Thickness

Dimensions Stock Part

UOM

416.1516x2x3BK	715411416066	Black	15/16 In. (24 mm)	2' x 3'	Y	EA
416.1516x3x10BK	715411165209	Black	15/16 In. (24 mm)	3' x 10'	N	EA
416.1516x3x5BK	715411416639	Black	15/16 In. (24 mm)	3' x 5'	Y	EA
416.1516x3x75BK	715411416950	Black	15/16 In. (24 mm)	3' x 75'	N	RL
416.1516x4x75BK	715411416028	Black	15/16 In. (24 mm)	4' x 75'	N	RL
416.916x2x3BK	715411417087	Black	9/16 In. (14 mm)	2' x 3'	Y	EA
416.916x2x75BK	715411416233	Black	9/16 In. (14 mm)	2' x 75'	N	RL
416.916x3x10BK	715411266890	Black	9/16 In. (14 mm)	3' x 10'	N	EA
416.916x3x5BK	715411416301	Black	9/16 In. (14 mm)	3' x 5'	Y	EA
416.916x3x75BK	715411416707	Black	9/16 In. (14 mm)	3' x 75'	N	RL
416.916x4x75BK	715411416929	Black	9/16 In. (14 mm)	4' x 75'	N	RL