



<https://wearwell.com/>

GRADE A® Food Production Anti-fatigue Workstation Floor Mat

Group 482

Designed to withstand fluids and oils including vegetable oils, animal fats, citrus, and fish oil. Textured surface increases traction when greasy and wet. Passes NSF test ASTM G21- 09 (2013) for resistance to microorganisms without any microbial additives. Ideal in food and beverage production and processing environments.

For fully modular Grade A, check out our ["Grade A LockSafe flooring"](#)

- U.S. PATENT NO. D609,050
- Meets the ASTM G21 standard for anti-microbial properties
- Rubber specially formulated for food and beverage production and processing
- Overall thickness 1/2" (13 mm)
- Built in handles for easy removal and cleaning
- Knob style under structure for superior drainage and support

Categories & Applications Anti-Fatigue Matting

Suitable Environment Wet Area, Oily

Customization Options Standard Sizes Only

Solid or Drainage Drainage

Material Grease Proof Nitrile Rubber

Recycled <10%

Warranty 2 Years

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	-20 to 250 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet: COF = .68
Compression Deflection	ASTM D575 - 17psi @ 25% =.12" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
482.12x30x36TC	715411482160	Terra Cotta	1/2 In. (13 mm)	30" x 36"	Y	EA
482.12x30x60TC	715411482535	Terra Cotta	1/2 In. (13 mm)	30" x 60"	Y	EA